



Service Bulletin

21

March 24, 1961

TO ALL DISTRIBUTORS AND DEALERS

SUBJECT: Facts About the New 1961 Rotary Mowers.

1. RMR3261 32" Rotary Mower for Models 401, 551, ST400 and ST550 tractors.

A. Use of Counter Balance Spring, Part #1129.

a. This spring is to be used to enable the mower to easily float on rough ground.

b. Under Normal Conditions Part #1129 can be eliminated.

B. Windmilling in down position when clutch is disengaged.

a. It is necessary to raise the mower to the Travel or Up position to eliminate windmilling.

b. All belts are made with a plus or minus 1/8" tolerance. After useage a marked difference will be noticed in the clutching effectiveness.

2. RMR3661 36" Rotary Mower for Model 701 Tractor.

A. Adjustment of Part #4114 (2) Hangers.

a. Release Part #1343 (2) Jam Nuts and turn Part #4114 (2) Hangers to tighten or loosen Part #1578 twin belts. Part #4114 (2) also controls the entire mower assembly with regard to positioning beneath the tractor frame. If not properly squared mower will jam against the tractor belt guard, Part #4202. It is important these adjustments be made at time of installation.

PARTS & SERVICE DEPARTMENT

WHEEL HORSE PRODUCTS, INC.

JW:md